



Technische Daten

- Einfachwirkend
- Belastet
- Drehrichtungsunabhängig
- Einzelfeder
- Elastomer-Balg

Einsatzgrenzen

d1 = 6 - 70 mm
 p = 6 bar
 t = -20 °C - 180 °C
 vg = 10 m/s

Werkstoffe

Gleitring: Kohle (Z32)
 Gegenring: Keramik (C)
 Elastomer: NBR (G)
 Andere Bauteile: Edelstahl (E)

d ₁	d ₃	d ₇	l ₃	l ₄
6	18,0	22,0	8,0	4,0
8a	20,0	26,0	11,0	4,0
8b	20,0	22,0	11,0	4,0
8c	24,0	26,0	11,0	8,0
9	24,0	26,0	11,0	8,0
10	24,0	26,0	11,0	8,0
11	24,0	26,0	11,0	8,0
12a	24,0	26,0	11,0	5,5
12b	24,0	26,0	13,0	8,0
12c	32,0	35,0	13,0	8,0
13	24,0	26,0	13,0	8,0
14a	28,0	25,0	13,0	7,0
14b	28,0	28,5	13,0	8,0
14c	32,0	29,5	13,0	8,0
14d	32,0	35,0	13,0	8,0
15a	32,0	29,5	13,0	8,0
15b	32,0	38,0	13,0	8,0
15c	35,0	38,0	13,0	8,0
16a	32,0	29,5	13,0	8,0
16b	35,0	38,0	13,0	8,0
16c	39,0	38,0	13,0	8,0
16d	39,0	42,0	13,0	8,0
17	39,0	42,0	13,0	8,0
18	39,0	42,0	13,0	8,0
19	39,0	42,0	13,0	8,0
20a	39,0	42,0	13,0	8,0
20b	42,0	45,0	13,0	10,0
22	42,0	45,0	13,0	10,0
23	47,0	50,0	14,0	10,0
24	47,0	50,0	14,0	10,0
25a	42,0	50,0	14,0	10,0
25b	47,0	50,0	14,0	10,0
26	47,0	50,0	14,0	10,0
28	54,0	57,0	15,0	10,0
30	54,0	57,0	15,0	10,0
32	54,0	57,0	15,0	10,0
35	60,0	63,0	16,0	10,0
38	65,0	68,0	18,0	12,0
40	65,0	68,0	18,0	12,0
45	70,0	73,0	20,0	12,0
50	85,0	88,0	23,0	15,0
55	85,0	88,0	23,0	15,0
60	105,0	110,0	30,0	15,0
70	105,0	110,0	32,0	15,0